

EASY BOND

HIGH QUANLITY TILE ADHESIVE



- **GOOD ADHESION**
- **EASY TO APPLY**
- **HIGH DURABILITY**



Lemax Easy Bond is a cement-based tile adhesive certified with C1 quality standards according to TCVN 7899-3:2008 and ISO 13007-3:2004, with many Properties-Advantages:

- High adhesion strength.
- Non shrinkage, non flaking.
- Good waterproofing.
- Easy to apply, economy & shorten the construction progress.
- Eco-friendly

Lemax Easy Bond is suitable for tiling and paving ceramic tiles, Granite, Mosaic, natural stone... medium size & water absorption, in covered interior or exterior areas. Areas with high humidity such as bathroom, kitchen...

FIELDS OF APPLICATION

Used for tiling Ceramic, Granite, Porcelain, Glass Mosaic, natural stone... large size and low water absorption on substrates:

- Floors or walls with plaster or screed.
- Concrete slabs or reinforced concrete slabs with elastic layer provided that these slabs are properly cured, given enough time and completely dry.
- Gypsum board has been treated with specialized lining.
- Interior tiling.
- Tiling the exterior area is less affected by sudden temperature changes

CONSUMPTION

Size (mm x mm)	Consumption (kg/m ²)
≤ 200 x 200	2 – 3 kg/m ²
300 x 300 / 400 x 400	4 – 5 kg/m ²
300 x 600 / 600 x 600	6 – 8 kg/m ²
600 x 900 / 800 x 800	8 – 10 kg/m ²

SPECIFICATIONS

Color	Grey
Shape	Powder
Packaging	25 Kg/ bag
Shelf life	12 month (in original)
Denisty	≈ 1.65 kg/l (dry) / ≈ 1.84 kg/l (wet)
Ratio	22% - 25%
Consumption	5-7 m ² /bag 25kg (thickness 3mm)
Apply time	60 min (65% & 27 °C)
Operating time	20 min
Waiting time before grouting	7-8 Hour (Walls) 24 Hour (Floors)
Standard condition adhesion strength	≥ 0.5 N/mm ²
Adhesion strength After soaking in water	≥ 0.5 N/mm ²
Adhesion strength after heat aging	≥ 0.5 N/mm ²

EASY BOND

HIGH QUALITY TILE ADHESIVE

GOOD ADHESION | EASY TO APPLY | HIGH DURABILITY

